cisco Meraki

GX20 Data Sheet

cisco Meraki

Datasheet | GX20

Meraki Go Security Gateway



Performance

- · Firewall Throughput 250 Mbp/s
- · Recommended for 50 clients of fewer

Interfaces

- WAN Interface: 1x 10/100/1000 BASE-T Ethernet (RJ45)
- LAN interfaces: 4x 10/100/1000 BASE-T Ethernet (RJ45)
- PoE: 1x 802.3af enabled port (15.5W)

Network and Security Services

- · Stateful firewall
- · Port Forwarding

Environment

- Operating temperature: 32 °F to 104 °F (0 °C to 40 °C)
- · Humidity: 5 to 95% non-condensing

•	ıні	טיי	CAN	/icae

 DNS based security powered by Cisco Umbrella (additional subscription required) Kensington lock hard point

Power

• 50W (54V / 0.92 A) Power Supply Included

LED Indicators

- · 2 Ethernet status
- 1 power/booting/firmware upgrade status

Physical Dimensions

6.83" x 4.41" x 1.0.4" (173.4mm x 112mm x 26.3mm), not including deskmount feet or mount plate

Warranty

· 1 year hardware warranty

In the Box

- GX20-HW: Meraki Go Security Gateway
- · Wall mount and screw kit
- · Quick start guide
- · PSU and ethernet cable

Model List / Accessories

GX20-HW-XX Security Gateway - Desktop

GA-PWR-50WAC 50W Replacement Laptop Style

Adapter for GX20

XX = US/UK/EU

Cisco Systems, Inc. | 500 Terry A. Francois Blvd, San Francisco, CA 94158 | (415) 432-1000 |



Business Solutions 1.800.800.0014 Enterprise Solutions 1.800.369.1047

www.connection.com/meraki

Public Sector Solutions 1.800.800.0019